



<b>Processor</b>	Intel Atom e-Menlow Processor 1.1/1.6 Ghz
<b>System Controller</b>	Intel SCH US15W
<b>SDRAM</b>	1GB DDR2-SDRAM
<b>Flash</b>	Up to 8GB NAND flash (128MB to 8GB)
<b>Front Panel</b>	<ul style="list-style-type: none"> <li>Two Gigabit Ethernet Ports</li> <li>Four USB 2.0 Ports</li> </ul>
<b>Debug Port</b>	XDP debug port
<b>DIP Switch</b>	16 TTL input signals
<b>PMC Interface</b>	32-Bit, 33/66 MHz PCI bus
<b>PMC P14 IO Interface</b>	<ul style="list-style-type: none"> <li>SDVO Display Port Interface</li> <li>Intel HD Audio Interface</li> <li>3 USB 2.0 High-speed ports</li> <li>SD Interface</li> <li>SM Bus Interface</li> <li>RS232 Interface</li> <li>10 GPIO's signals</li> </ul>
<b>OS &amp; Software Support</b>	<ul style="list-style-type: none"> <li>Linux OS drivers (Ubuntu, Fedora7)</li> <li>Windows XP drivers</li> <li>Windows XP embedded drivers</li> <li>WES 2009</li> </ul>
<b>BIOS support</b>	AMI BIOS
<b>Physical Characteristics</b>	<ul style="list-style-type: none"> <li>Conduction-cooled PMC form factor</li> <li>149mm x 79mm dimension</li> </ul>
<b>Power Input</b>	5V, 2A From PrPMC carrier board or standalone
<b>Power consumption</b>	Typically 7W

For further details, contact [mktg@iwavesystems.com](mailto:mktg@iwavesystems.com)